

FluidPRO™ ATX Automatic Transmission Fluid Exchangers

The most technologically advanced transmission service machines. Fast, automatic and accurate fluid exchange!



Control Panel

- Electronic diode illuminated keypad, intuitive operation
- Simple automatic fluid level adjustment. Plus or minus 1/2 quart adjustment keys
- Used & new fluid sight glasses
- Transmission diagnostic pressure gauge
- Fluid flow direction indicator, verifies correct hook-up
- Push button drain function

Color-Coded Adapter/Coupler Set

- Included w/ every ATX unit
- Stored on top of unit for EZ access
- Includes application guide



Specifications

Electrical	12 VDC - 15 Amp (ATX-3 12 VDC - 17 Amp)
Dimensions	45 in x 28 in x 26.5 in (112 cm x 70 cm x 67 cm) (H x W x D)
Weight	ATX-2:158 lb (72 kg) / ATX-2 + Boost:162 lb (74 kg) ATX-3: 164 lbs. (74.5 kg)
Operating Range	32° to 122°F (0° to 50°C)
Pump	Positive Displacement Gear Pump, 4 quarts (3.8 liters) per minute / ATX-3 also includes Diaphragm Pump, 7.2 quarts (6.84 liters) per min. ATX-2 + Boost includes additional Diaphragm Pump, 7.2 quarts (6.84 liters) per min to increase fluid suction rate in low-flow/temperature controlled transmissions.
Process Time	2 to 5 minutes average full exchange. ATX-3 also offers (Dipstick Mode) 8 to 14 minutes average full exchange
Scale Accuracy	±0.03% over usable range
Controls	Microprocessor with digital keypad & light emitting diodes
Fluid Tanks	26 quarts (24.6 liters) each for both new & used fluids
Fluid Types	Multiple Fluid Capability
Hoses	10 ft (3 m) Black & Red (Exchange); 8 ft (2.5 m) Black (Empty Used Tank) / ATX-3 also includes 5 ft (1.5 m) Clear, attached to 8 ft (2.5 m) Black Hose for Dipstick Mode
Adapter Set	Cooler line connection. Valved couplers for minimum spill. Standard adapters for Ford, GM, Chrysler, & Universal (most Asian imports).
Warranty	1 Year Parts & Labor



ATX-2PS Combo

- ATX-2 w/ mounted PSX-2
- For simultaneous transmission & power steering service
- See PSX-2 for unit specifications