

A/C Adapters, Couplers, Cylinders, Fittings and Hoses

R12 Adapter Kit, Basic P/N 218020

1/4 in. x 1/4 in. shutoff
1/4 in. x 3/16 in. shutoff
GM 1991 and later
1/4 in. x 3/16 in. Flexible
1/4 in. x 1/8 in. adapter
Misc. gaskets, depressors



GM '91 High Side Adapter, P/N 218025

Special R12 High Side adapter for 1991 and later GM vehicles.



R134a Tank Adapter, P/N 218008

Special fitting to be screwed onto 1/2 in. ACME threads, so that R134a Low Side Field Service Coupler can be attached to a virgin or recycle tank.



Vacuum Pump Adapter P/N 217025

R134a Vacuum Pump Adapter, 1/4 in. Flare female x 1/2 in. ACME male.



Red High Side Service Coupler P/N 215010

Fits all machines and gauge sets requiring R134a High Side connection. 1/2 in. ACME threads connect to hose ends.



Blue Low Side Service Coupler P/N 215011

Fits all machines and gauge sets requiring R134a Low Side connections. 1/2 in. ACME threads connect to hose ends.



R12/R22 DOT Cylinder, 30 lb. P/N 219710

R12/R22 DOT Cylinder, 30 lb. (P/N 219710). Standard "re-usable" DOT container. Rated for the extra high pressures of R22. 1/4 in. SAE connections. Recommend Electronic Weight Scale as additional accessory to avoid over-filling.



R12/R22 DOT Cylinder, 30 lb. with OFP P/N 219711

R12/R22 DOT Cylinder, 30 lb. with OFP (P/N 219711). Over-fill Protection float switch installed. Compatible with RTI equipment or others that use Brad Harrison type electrical connector.

R134a DOT Cylinder, 30 lb. P/N 219714

R134a DOT Cylinder, 30 lb. (P/N 219714). Standard "re-usable" DOT container. 1/2 in. ACME connections. Recommend Electronic Weight Scale as additional accessory to avoid over filling.



R134a DOT Cylinder, 30 lb., with OFP P/N 219715

Overfill Protection float switch installed. Compatible with RTI equipment or others that use Brad Harrison type electrical connector.

Heat Blanket P/N 215020

Specially designed by RTI for adding heat to refrigerant containers to increase speed of transfer (pre-charging) into RTI machines or charging from refrigerant containers. 100–120 Volt. Thermostatically controlled with thermal fuse for safety. Fits 30 lb. and 50 lb. containers. Recommended in cold climates.



R134a, Red Hose, 20 ft., P/N 219510

Special RTI Low Permeability 20 ft. long red high side service hose. Works on all R134a machines and gauge sets. (1/2 in. ACME x 14 mm)



R134a, Blue Hose, 20 ft., P/N 219511

Special RTI Low Permeability 20 ft. long blue low side service hose. Works on all R134a machines and gauge sets. (1/2 in. ACME x 14 mm)



R12 Yellow Hose, 8 ft., Ball Valve P/N 219538

R12 yellow hose, 8 ft., 1/4 in. turn, shut-off valve. (1/4 in. flare female x 1/4 in. flare female)



R12 Yellow Hose, 6 in., Shut-off Valve P/N 219540

6 in. yellow hose assembly with 1/4 in. turn valve. (1/4 in. flare male x 1/4 in. flare female)



R12 Hose Set, 6 in., Shut-off Valve P/N 219543

One each red and blue
6 in. hose assembly with 1/4 in. turn valve. (1/4 in. flare male x 1/4 in. flare female)

